

Notic of Referenc s Cited

| Application/Control No. | U | | Applicant(s)/Patent Under | | |
|-------------------------|---|---|---------------------------------|-------------|--|
| 09/667,775 | | | Reexamination KAWANISHI ET A | AL. | |
| Examiner | | | Art Unit | | |
| Johannes P Mondt | | ļ | 2826 | Page 1 of 1 | |

U.S. PATENT DOCUMENTS

| * | | Document Number Country Code-Number-Kind Code | Date MM-YYYY | Name | Classification |
|----------|---|--|-----------------|-----------------|----------------|
| | Α | US-5,907,571 | 05-1999 | Ogino et al. | 372/43 |
| | В | US-5,355,385 | 10-1994 | Amano et al. | 372/49 |
| | С | US-5,970,081 | 10-1999 | Hirayama et al. | 372/96 |
| | D | US-5,422,905 | 06-1995 | Andrews | 372/50 |
| | Е | US-5,625,402 | 04-1997 | Sarraf | 347/232 |
| | F | US-6,049,125 | 04-2000 | Brooks et al. | 257/712 |
| | G | US- | | | |
| | Н | US- | | | |
| | 1 | US- | | | |
| | J | US- | | | |
| | к | US- | | | |
| | L | US- | | | |
| <u> </u> | м | US- | | | |

FOREIGN PATENT DOCUMENTS

| * | | Document Number Country Code-Number-Kind Code | Date MM-YYYY | Country | Name | Classification |
|---|---|--|-----------------|---------|------|----------------|
| | N | | | | | |
| | 0 | | | | | |
| | Р | , | | | | |
| | Q | | | | | |
| | R | | | | | |
| | s | | | | | |
| | Т | | | | | |

NON-PATENT DOCUMENTS

| * | | Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages) |
|---|---|--|
| | υ | Claisse, P.R. et al., "Internal Quantum Efficiency of Laser Diodes", Electronics Letters, Volume 28, No. 21, pp. 1991-1992 (1992). |
| | ٧ | Missagia, L.J., et al, "Microchannel Heat Sinks for Two-Dimensional High-Power-Density Diode Laser Arrays", IEEE J. Quantum Electronics, Volume 25 (9), September 1989, pp. 1988-1992. |
| | w | Hazell, J.F., et al, "The Effect of Varying Barrier Height on the Operational Characteristics of 1.3 micron Strained-Layer MQW Lasers", IEEE J. Quantum Electroncis, Volume 34 (12), December 1998, pp.2358-2363. |
| | х | Kudo, K. et al, "1.52-1.59 micron Range Different-Wavelength Modulator-Integrated DBF-LDs Fabricated on a Single Wafer", in "Integrated Optics and Optical Fibre Communications" (Int. Conf. on -), 22-25 Sept. '97 Edinburgh, UK (Volume 5, pp. 49-52). |

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)

Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.